CHARACTERISATIONS THE BIO-ACTIVE COMPOUNDS OF BIO-OIL EXTRACTED FROM RED MERANTI SAWDUST BY FAST PYROLYSIS

NOR WAHIDATUL AZURA BINTI ZAINON NAJIB

DOCTOR OF PHILOSOPHY

UNIVERSITI MALAYSIA PAHANG

SUPERVISOR'S DECLARATION

We hereby declare that we have checked this thesis and in our opinion, this thesis is adequate in terms of scope and quality for the award of the degree of Doctor of Philosophy.

_____

(Supervisor's Signature)

Full Name : PROFESSOR DATO' DR. ZULARISAM BIN AB WAHID

Position : PROFESSOR

Date : 10 AUGUST 2018

_____

(Co-supervisor's Signature)

Full Name : PROFESSOR DATIN DR. MIMI SAKINAH BINTI ABDUL MUNAIM

Position : PROFESSOR

Date : 10 AUGUST 2018

STUDENT'S DECLARATION

I hereby declare that the work in this thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at Universiti Malaysia Pahang or any other institutions.

_____

(Student's Signature)

Full Name : Nor Wahidatul Azura binti Zainon Najib

ID Number : PKE 13003

Date : August 2018

CHARACTERISATIONS THE BIO-ACTIVE COMPOUNDS OF BIO-OIL EXTRACTED FROM RED MERANTI SAWDUST BY FAST PYROLYSIS

NOR WAHIDATUL AZURA BINTI ZAINON NAJIB

Thesis submitted in fulfillment of the requirements
for the award of the degree of
Doctor of Philosophy

Faculty of Engineering Technology

UNIVERSITI MALAYSIA PAHANG

AUGUST 2018

ACKNOWLEDGEMENTS

All praises to Allah S.W.T, The Almighty God and The Lord of the Universe, The Merciful and Gracious for His mercy has given me the strength, blessing and time to complete this study. Salam to our beloved prophet, Nabi Muhammad s.a.w.

Special thanks to my sponsors, Universiti Malaysia Perlis (UniMAP) and Ministry of Higher Education (KPT) for their financial support throughout my study.

I am grateful and would like to express my sincere gratitude to my supervisor Professor Dato' Dr. Zularisam bin Ab Wahid for his germinal ideas, invaluable guidance, continuous encouragement and constant support in making this research possible. He has always impressed me with his outstanding professional conduct, his strong conviction for science, and his belief that a PhD program is only a start of a life-long learning experience. I appreciate his consistent support from the first day I applied to graduate program to these concluding moments. I am truly grateful for his progressive vision about my training in engineering technology, his tolerance of my naïve mistakes, and his commitment to my future career. I also sincerely thanks for the time spent proofreading and correcting my many mistakes.

It gives me great pleasure to acknowledge to the guidance, valuable suggestions, constructive criticism and incredible patience of my co-supervisor, Professor Datin Dr. Mimi Sakinah binti Abdul Munaim. Your scientific excitement inspired me in the most important moment of making right decisions and has significantly contributed to this thesis. Thanks you for trusting me.

My sincere thanks go to all my lab mates and members of the staff of Faculty of Engineering Technology Department, UMP, who helped me in many ways and made my stay at UMP pleasant and unforgettable. Many special thanks go to member research group for their excellent co-operation, inspiration and support during this study.

Finally, I acknowledge my sincere indebtedness and gratitude to my beloved husband and my child, my parents and sibling for their love, dream and sacrifice throughout my study and life. I cannot find the appropriate words that could properly describe my appreciation for their devotion, support and faith in my ability to attain my goals. Special thanks should be given to my friends, lab mates and postgrad roommates with their supports, comments, suggestions and knowledge, which has crucial for the successful completion of this study. For the name mentioned and not mentioned that have involved throughout my study, only Allah could pay your kindness. Last but not least, I hope this study would give a beneficial input in this field especially in conducting the future study.

ABSTRAK

Pirolisis pantas ialah satu teknologi penukaran habakimia untuk menukar biojisim kepada produk bio-minyak. Dalam kajian ini, habuk meranti merah (RMS) dipilih sebagai biojisim suapan untuk menilai potensinya menghasilkan bio-minyak melalui pirolisis pantas. Kajian ini merangkumi objektif untuk menyiasat kesan parameter proses dalam mengoptimumkan penghasilan bio-minyak dan mencirikan bio-minyak yang diekstrak. Pirolisis cepat dijalankan dalam skala-makmal reaktor lapisan terbendalir, bersama sistem yang terdiri dari pengawal suhu, siklon, pemeluwap, gas nitrogen, meter alir and pengumpul arang dan bio-minyak. Dalam mengkaji kesan keadaan pirolisis, eksperimen dijalankan mengikut pendekatan satu-faktor-pada-satu-masa (OFAT) dengan parameter yng terlibat ialah suhu, kadar alir N_2, masa tahanan dan saiz partikel suapan. Keputusan menunjukkan bio-oil mencapai hasil maksimum sekitar 56.3 % pada suhu 450 °C, kadar alir N_2 25 L/min dan masa tahanan 20 min. untuk saiz partikel suapan 0.3 mm. Dapat disimpulkan bahawa suhu adalah parameter yang paling berpengaruh untuk hasilan bio-minyak. Pencirian fizikokimia bio-minyak menunjukkan bio-minyak tidak sesuai untuk bahan bakar pengangkutan kerana tinggi kandungan oksigen. Melalui analisis spektrometri kromatografi gas (GC-MS), fenolik adalah sebatian dominan yang dikenalpasti dalam bio-minyak. Jumlah gula dalam bio-minyak ialah 12.82 % luas termasuk hasil levoglucosan adalah 8.97 % luas. Dalam menentukan kesan rawatan basuhan biojisim, RMS dibasuh dengan air dinyahion (DI) atau asid hidroklorik (HCl) cair. Kecekapan penyingkiran AAEM dengan air DI, 1.0M HCl dan 2.0 M HCl adalah 66.39%, 93.32% dan 97.28%, masing-masing. Dari analisis FTIR, rawatan basuhan telah menguatkan ikatan kimia RMS. Untuk pengeluaran bio-minyak, bio-minyak yang diekstrak dari RMS - air DI mencapai hasil maksimum kira-kira 57.2 % pada 450 °C suhu optimum. Dalam bio-minyak yang diekstrak, RMS yang dibasuh menghasilkan lebih banyak kompaun berat dan lebih banyak levoglucosan daripada RMS mentah. Dalam kajian pyrolysis RMS yang diresapi, RMS diresapkan dengan $CaCl_2$, $CaSO_4$, $FeCl_2$ atau $FeSO_4$. Antara suapan ini, RMS - $FeSO_4$ meningkatkan proses penguraian pada suhu yang lebih rendah dengan suhu penguraian maksimum telah beralih dari 361 °C bagi RMS kawalan kepada 314 °C bagi RMS - $FeSO_4$. Melalui FTIR, resapan RMS dengan $FeSO_4$ telah melemahkan ikatan kimia dalam RMS. Dalam bio-minyak yang diekstrak, ia mengandungi sebatian berat molekul berjulat besar dan menunjukkan peningkatan dalam hasil levoglucosan. Levoglucosan adalah tertinggi dalam RMS - $FeSO_4$ iaitu 40.23 % luas, dengan hasil gula sebanyak 42.24 % luas. Dalam mengoptimumkan hasil bio-minyak, rekabentuk komposit pusat (CCD) daripada kaedah pemodelan permukaan respon (RSM) digunakan untuk membangunkan model matematik dan mengoptimumkan parameter proses. Melalui model yang diramalkan, keputusan menunjukkan keadaan proses pirolysis optimum diperoleh pada suhu 480 °C, 25 L/min kadar aliran N_2 dan 24 min masa tahanan dengan 56.5 % hasil bio-minyak dan 2.11 % ralat oleh eksperimen. Kesimpulannya, RMS mempunyai potensi untuk menghasilkan bio-minyak. Dengan rawatan lanjut ke atas bio-oil untuk menyingkirkan kandungan oksigen, bio-minyak ini boleh digunakan untuk menggantikan bahan api konvensional. Rawatan terapi RMS dengan $FeSO_4$ mendedahkan bahawa proses penguraian dapat ditingkatkan pada suhu yang lebih rendah dan meningkatkan levoglucosan dalam bio-minyak. Penemuan-penemuan ini dijangka menyediakan beberapa garis panduan dalam kajian masa depan untuk menghasilkan produk tambah nilai dari sisa lignoselulosa yang lain dan seterusnya, konsep kerajaan untuk mengalihkan sisa kepada produk-kekayaan dapat dicapai.

ABSTRACT

Fast pyrolysis is a thermochemical conversion technology to convert biomass into bio-oil product. In this study, red meranti sawdust (RMS) was selected as biomass as feedstock to evaluate its potential to produce bio-oil by fast pyrolysis. The study covers the objective to investigate the parameters effect of process in optimising the bio-oil production and characterise the extracted bio-oil. Fast pyrolysis process was conducted in a bench-scale fluidized bed reactor, with the system consist of temperature controller, cyclone, condensers, nitrogen gas, flow meter, char and bio-oil collectors. In investigating the effect of pyrolysis condition, the experiments were run according to one-factor-at-a-time (OFAT) approach with the parameters involved were temperature, N_2 flow rate, retention time and feed particles size. Results showed that bio-oil achieved maximum yield about 56.3 % at 450 °C of temperature, 25 L/min of N_2 flow rate and 20 min of retention time for 0.3 mm of feed particles size. It can be concluded that the temperature was the most influential parameter for bio-oil yield. Physicochemical characterisation of bio-oil indicated bio-oil not suitable for transportation fuel due to high oxygen content. Through gas chromatography–mass spectrometry (GC-MS) analysis, phenolic was the dominant compound identified in bio-oil. Total sugars in bio-oil was 12.82 % area including levoglucosan yield was 8.97 % area. In determining the effect of washing treatment, RMS was washed with deionised (DI) water or diluted hydrochloric (HCl) acid. The efficiency of AAEM removal by DI water, 1.0M HCl and 2.0 M HCl were 66.39 %, 93.32 %, and 97.28 %, respectively. From FTIR analysis, washing treatment had strengthened the RMS chemical bonds. For bio-oil production, bio-oil extracted from RMS - DI water achieved maximum yield about 57.2 % at 450 °C of optimum temperature. In extracted bio-oil, washed RMS produced higher heavier compound and higher levoglucosan than raw RMS. In pyrolysis of impregnated RMS study, RMS was impregnated with $CaCl_2$, $CaSO_4$, $FeCl_2$ or $FeSO_4$. Among these feedstocks, RMS - $FeSO_4$ enhanced the degradation process at lower temperatures with the maximum degradation of temperature has been shifted from 361 °C for RMS control to 314 °C for RMS - $FeSO_4$. Through FTIR analysis, impregnated RMS with $FeSO_4$ has weakened the RMS chemical bond. In extracted bio-oil, it consisted large range of molecular weight compounds and showed an increasing in levoglucosan yield. Levoglucosan was the highest in RMS - $FeSO_4$ about 40.23 % area, with 42.24 % area of total anhydrosugars yield. In optimising bio-oil yield, central composite design (CCD) of response surface methodology (RSM) modelling was employed to develop mathematical model and optimise the process parameters. Through predicted model, results showed that the optimal pyrolysis process condition was obtained at 480 °C of temperature, 25 L/min of N_2 flow rate and 24 min of retention time with 56.5 % of bio-oil yield and 2.11 % of error by experiment. Conclusion, RMS has a potential to produce bio-oil. With further treatment on bio-oil to remove oxygen content, this bio-oil can be applied to substitute conventional fuel. Impregnated treatment of RMS with $FeSO_4$ reveals degradation process can be enhanced at lower temperature and increases levoglucosan in bio-oil. These findings are expected to provide some guidelines in future study to produce value-added product from other lignocellulose waste and further, the government concept of divert waste to wealth-product can be achieved.

TABLE OF CONTENT

LIST OF TABLES

LIST OF FIGURES

LIST OF SYMBOLS

°C	degree Celsius
°C/s	degree Celsius per Second
cSt	centistokes
g/mol	gram/mol
kJ/kg	Kilojoule/kilogram
L/min	Litre per minute
m^3	cubic meter
min	minute
mL	mililitre
mm	millimetre
MJ/kg	Megajoule/kilogram
Mtoe	Million tons of oil equivalent
rpm	Rotation per Minute
wt. %	percentage by weight
W/mK	Watts per meter Kelvin
µm	micrometre
Y_b	bio-oil yield

LIST OF ABBREVIATIONS

AAEM	Alkali and Alkaline Earth Metal
ASEAN	Association of Southeast Asian Nations
ASTM	American Society for Testing and Materials
BC	Bio-oil Collector
C	Carbon
Ca	Calcium
$CaCl_2$	Calcium Chloride
$CaSO_4$	Calcium Sulphate
CC	Char Collector
CCD	Central Composite Design
CO	Carbon Monoxide
CO_2	Carbon Dioxide
DI	Deionised
DTG	Differential Thermogravimetric
ENSYN	Renewable Fuels and Chemical from Non-Food Biomass
$FeCl_2$	Iron (II) Chloride
$FeSO_4$	Iron (II) Sulphate
FTeK	Fakulti Teknologi Kejuruteraan
FTIR	Fourier Transform Infrared Spectroscopy
GC-MS	Gas Chromatography – Mass Spectrometry
H^+	Hydrogen Ion
H_2	Hydrogen Gas
H_2O	Water
HAA	Hydroxyacetaldehyde
HCl	Hydrochloride Acid
HHV	Higher Heating Value
ICP-OES	Inductively Coupled Plasma – Optical Emission Spectroscopy
K	Potassium
LHV	Lower heating value
Mg	Magnesium
N_2	Nitrogen Gas
Na	Sodium
NCG	Non-Condensable Gases
NO_x	Nitric Oxide and Nitrogen Dioxide

NREL	National Renewable Energy Laboratory
O	Oxygen
OFAT	One Factor at a Time
PAH	Polycyclic Aromatic Hydrocarbon
pH	Potential of Hydrogen
RMS	Red Meranti Sawdust
RSM	Response Surface Methodology
TGA	Thermogravimetric Analysis
UMP	Universiti Malaysia Pahang
Zn	Zink

REFERENCES

Abdullah, N., & Gerhauser, H. (2008). Bio-oil derived from empty fruit bunches. *Fuel*, *87*, 2606–2613. https://doi.org/10.1016/j.fuel.2008.02.011

Abnisa, F., Wan Daud, W.M., & Sahu, J. (2011). Optimization and characterization studies on bio-oil production from palm shell by pyrolysis using response surface methodology. *Biomass and Bioenergy*, *35*(8), 3604–3616. https://doi.org/10.1016/j.biombioe.2011.05.011

Açıkalın, K., Karaca, F., & Bolat, E. (2012). Pyrolysis of pistachio shell: Effects of pyrolysis conditions and analysis of products. *Fuel*, *95*, 169–177. https://doi.org/10.1016/j.fuel.2011.09.037

Adam, J., Blazso, M., Meszaros, E., Stocker, M., Nilsen, M.H., Bouzga, A., Hustad, J.E., Gronli, M., & Oye, G. (2005). Pyrolysis of biomass in the presence of Al-MCM-41 type catalysts. *Fuel*, *84*, 1494–1502. https://doi.org/10.1016/j.fuel.2005.02.006

Agblevor, F.A., Besler, S., & Wiselogel, A.E. (1995). Fast Pyrolysis of Stored Biomass Feedstocks. *Energy & Fuels*, *9*(3), 635–640. https://doi.org/10.1021/ef00052a010

Akhtar, J., & NorAishah, S.A. (2012). A review on operating parameters for optimum liquid oil yield in biomass pyrolysis. *Renewable and Sustainable Energy Reviews*, *16*(7), 5101–5109. https://doi.org/10.1016/j.rser.2012.05.033

Azeez, A.M., Meier, D., Odermatt, J., & Willner, T. (2010). Fast pyrolysis of African and European lignocellulosic biomasses using Py-GC/MS and fluidized bed reactor. *Energy and Fuels*, *24*(3), 2078–2085. https://doi.org/10.1021/ef9012856

Balat, M., Balat, M., Kirtay, E., & Balat, H. (2009). Main routes for the thermo-conversion of biomass into fuels and chemicals. Part 1: Pyrolysis systems. *Energy Conversion and Management*, *50*(12), 3147–3157. https://doi.org/10.1016/j.enconman.2009.08.014

Ballesteros, I., Ballesteros, M., Cara, C., Saez, F., Castro, E., Manzanares, P., Negro, M.J., & Oliva, J.M. (2011). Effect of water extraction on sugars recovery from steam exploded olive tree pruning. *Bioresource Technology*, *102*(11), 6611–6616. https://doi.org/10.1016/j.biortech.2011.03.077

Beis, S.H., Onay, O., & Kockar, O.M. (2002). Fixed-bed pyrolysis of safflower seed: influence of pyrolysis parameters on product yields and compositions. *Renewable Energy*, *26*, 21–32.

Biewer, M.C. (2011). Structure Determination. Retrieved September 5, 2017, from http://www.utdallas.edu/~biewerm/9H-analytical.pdf

Biomass Fuel Analysis For Energy Crop (Closed-Loop) and Wood Derived Fuel/Yardwaste (Open-Loop). (2015). Retrieved April 9, 2015, from http://www.treepower.org/fuels/analysis.html

Blanco López, M.C., Blanco, C.G., Martínez-Alonso, A., & Tascón, J.M.D. (2002). Composition of gases released during olive stones pyrolysis. *Journal of Analytical and Applied Pyrolysis*, *65*(2), 313–322. https://doi.org/10.1016/S0165-2370(02)00008-6

Boroson, M.L., Howard, J.B., Longwell, J. P., & Peters, W.A. (1989). Product yields and kinetics from the vapor phase cracking of wood pyrolysis tars. *AIChE Journal*, *35*(1), 120–128. https://doi.org/10.1002/aic.690350113

Boucher, M.E., Chaala, A., Pakdel, H. & Roy, C. (2000). Bio-oils obtained by vacuum pyrolysis of softwood bark as a l,iquid fuel for gas turbines. Part II: Stability and ageing of bio-oil and its blends with methanol and a pyrolytic aqueous phase. *Biomass and Bioenergy*, *19*(5), 351–361. https://doi.org/10.1016/S0961-9534(00)00044-1

Box, G.E.P., & Wilson, K.B. (1951). On the Experimental Attainment of Optimum Conditions. *Journal of the Royal Statistical Society. Series B (Methodological)*, *13*(1), 1–45.

Bridgwater, A.V., & Bridge, S.A. (1991). A Review of Biomass Pyrolysis and Pyrolysis Technologies. In *Biomass Pyrolysis Liquids. Upgrading and Utilisation* (pp. 11–92). https://doi.org/10.1007/978-94-011-3844-4_2

Bridgwater, A.V., & Peacocke, G.V.C. (1994). Engineering Developments in Fast Pyrolysis for Bio-oil. In *Proceeding Biomass Pyrolysis Oil Properties and Combustion Meeting, NREL* (pp. 110–127).

Bridgwater, A.V., Meier, D., & Radlein, D. (1999). An overview of fast pyrolysis of biomass. *Organic Geochemistry*, *30*(12), 1479–1493. https://doi.org/10.1016/S0146-6380(99)00120-5

Bridgwater, A.V. (1999). Principles and practice of biomass fast pyrolysis processes for liquids. *Journal of Analytical and Applied Pyrolysis*, *51*(1), 3–22. https://doi.org/10.1016/S0165-2370(99)00005-4

Bridgwater, A.V., & Peacocke, G.V.C. (2000). Fast pyrolysis processes for biomass. *Renewable and Sustainable Energy Reviews*, *4*, 1–73.

Bridgwater, A.V. (2012). Review of fast pyrolysis of biomass and product upgrading. *Biomass and Bioenergy*, *38*, 68–94. https://doi.org/10.1016/j.biombioe.2011.01.048

Buckley, T. J. (1991). Calculation of higher heating values of biomass materials and waste components from elemental analyses. *Resources, Conservation and Recycling*, *5*(4), 329–341.

Butler, E., Devlin, G., Meier, D., & McDonnell, K. (2011). A review of recent laboratory research and commercial developments in fast pyrolysis and upgrading. *Renewable and Sustainable Energy Reviews*, *15*(8), 4171–4186. https://doi.org/10.1016/j.rser.2011.07.035

Chaala, A., Ba, T., Garcia-Perez, M., & Roy, C. (2004). Colloidal properties of bio-oils obtained by vacuum pyrolysis of softwood bark: Aging and thermal stability. *Energy and Fuels*, *18*(5), 1535–1542. https://doi.org/10.1021/ef030156v

Chaiwat, W., Hasegawa, I., Kori, J., & Mae, K. (2008). Examination of degree of cross-linking for cellulose precursors pretreated with acid/hot water at low temperature. *Industrial and Engineering Chemistry Research*, *47*(16), 5948–5956. https://doi.org/10.1021/ie800080u

Chang, S.W., & Shaw, J.F. (2009). Biocatalysis for the production of carbohydrate esters. *New Biotechnology*, *26*(3–4), 109–116. https://doi.org/10.1016/j.nbt.2009.07.003

Chiaramonti, D., Oasmaa, A., & Solantausta, Y. (2007). Power generation using fast pyrolysis liquids from biomass. *Renewable and Sustainable Energy Reviews*, *11*(6), 1056–1086. https://doi.org/10.1016/j.rser.2005.07.008

Choi, H.S., Choi, Y.S., & Park, H.C. (2012). Fast pyrolysis characteristics of lignocellulosic biomass with varying reaction conditions. *Renewable Energy*, *42*, 131–135. https://doi.org/10.1016/j.renene.2011.08.049

Cindy, P.C.F., & David, J.L. (1993). Potential Applications and Markets for Biomass-Derived Levoglucosan. In *Advances in Thermochemical Biomass Conversion* (pp. 1484–1494).

Clark, J.H. (2007). Green chemistry for the second generation biorefinery—sustainable chemical manufacturing based on biomass. *JOURNAL OF CHEMICAL TECHNOLOGY & BIOTECHNOLOGY*, *82*(7), 603–609.

Collard, F.X., Blin, J., Bensakhria, A., & Valette, J. (2012). Influence of impregnated metal on the pyrolysis conversion of biomass constituents. *Journal of Analytical and Applied Pyrolysis*, *95*, 213–226. https://doi.org/10.1016/j.jaap.2012.02.009

Collard, F.X., & Blin, J. (2014). A review on pyrolysis of biomass constituents: Mechanisms and composition of the products obtained from the conversion of cellulose, hemicelluloses and lignin. *Renewable and Sustainable Energy Reviews*, *38*, 594–608. https://doi.org/10.1016/j.rser.2014.06.013

Cornerstone Analytical Libraries. (2017). Retrieved November 24, 2017, from http://www.cornerstoneanalytical.com/infrared-spectroscopy/

Coulson, M. (2006). Pyrolysis of Parennial Grasses from Southern Europe. *Pyne Newsletter*, 6–7.

Czernik, S., & Bridgwater, A.V. (2004). Overview of applications of biomass fast pyrolysis oil. *Energy and Fuels*, *18*(2), 590–598. https://doi.org/10.1021/ef034067u

Demirbaş, A. (2000). Mechanisms of liquefaction and pyrolysis reactions of biomass. *Energy Conversion and Management*, *41*(6), 633–646. https://doi.org/10.1016/S0196-8904(99)00130-2

Demirbas, A., & Arin, G. (2002). An Overview of Biomass Pyrolysis. *Energy Sources*, *24*(5), 471–482. https://doi.org/10.1080/00908310252889979

Demirbas, A. (2004). Effect of initial moisture content on the yields of oily products from pyrolysis of biomass. *Journal of Analytical and Applied Pyrolysis*, *71*(2), 803–815. https://doi.org/10.1016/j.jaap.2003.10.008

Demirbaş, A. (2005). Relationship between Initial Moisture Content and the Liquid Yield from Pyrolysis of Sawdust. *Energy Sources*, *27*(9), 823–830. https://doi.org/10.1080/00908310490479042

Di Blasi, C. (2002). Modeling intra- and extra-particle processes of wood fast pyrolysis. *AIChE Journal*, *48*(10), 2386–2397.

Di Blasi, C., Carmen, B., & Antonio, G. (2007). Effects of Diammonium Phosphate on the Yields and Composition of Products from Wood Pyrolysis. *Industrial & Engineering Chemistry Research*, *46*(2), 430–438.

Di Blasi, C., Branca, C., & Galgano, A. (2008). Thermal and catalytic decomposition of wood impregnated with sulfur- and phosphorus-containing ammonium salts. *Polymer Degradation and Stability*, *93*(2), 335–346. https://doi.org/10.1016/j.polymdegradstab.2007.12.003

Dickerson, T., & Soria, J. (2013). Catalytic Fast Pyrolysis: A Review. *Energies*, *6*(1), 514–538. https://doi.org/10.3390/en6010514

Diebold, J.P., & Bridgwater, A.V. (1997). Overview of Fast Pyrolysis of Biomass for the Production of Liquid Fuels. In *Developments in Thermochemical Biomass Conversion* (pp. 5–23). Springer Netherlands. https://doi.org/10.1007/978-94-009-1559-6_1

Eibner, S., Broust, F., Blin, J., & Julbe, A. (2015). Catalytic effect of metal nitrate salts during pyrolysis of impregnated biomass. *Journal of Analytical and Applied Pyrolysis*, *113*, 143–152. https://doi.org/10.1016/j.jaap.2014.11.024

Ellens, C.J., & Brown, R.C. (2012). Optimization of a free-fall reactor for the production of fast pyrolysis bio-oil. *Bioresource Technology*, *103*(1), 374–380. https://doi.org/10.1016/j.biortech.2011.09.087

Eom, I.Y., Kim, K.H., Kim, J.Y., Lee, S.M., Yeo, H.M., Choi, I.G., & Choi, J.W. (2011). Characterization of primary thermal degradation features of lignocellulosic biomass after removal of inorganic metals by diverse solvents. *Bioresource Technology*, *102*(3), 3437–3444. https://doi.org/10.1016/j.biortech.2010.10.056

Eom, I-Y., Kim, J-Y., Kim, T-S., Lee, S-M., Choi, D., Choi, I-G., & Choi, J.-W. (2012). Effect of essential inorganic metals on primary thermal degradation of lignocellulosic biomass. *Bioresource Technology*, *104*, 687–694. https://doi.org/10.1016/j.biortech.2011.10.035

Eric Meier. (2015). *WOOD! Identifying and Using Hundreds of Woods Worldwide*. The Wood Database.

Fahmi, R., Bridgwater, A.V., Darvell, L.I., Jones, J. M., Yates, N., Thain, S., & Donnison, I. S. (2007). The effect of alkali metals on combustion and pyrolysis of Lolium and Festuca grasses, switchgrass and willow. *Fuel*, *86*(10–11), 1560–1569. https://doi.org/10.1016/j.fuel.2006.11.030

Fahmi, R., Bridgwater, A.V., Donnison, I., Yates, N., & Jones, J.M. (2008). The effect of lignin and inorganic species in biomass on pyrolysis oil yields, quality and stability. *Fuel*, *87*(7), 1230–1240. https://doi.org/10.1016/j.fuel.2007.07.026

Fisher, T., Hajaligol, M., Waymack, B., & Kellogg, D. (2002). Pyrolysis behavior and kinetics of biomass derived materials. *Journal of Analytical and Applied Pyrolysis*, *62*(2), 331–349. https://doi.org/10.1016/S0165-2370(01)00129-2

Fratini, E., Bonini, M., Oasmaa, A., Solantausta, Y., Teiseira, J., & Baglioni, P. (2006). SANS analysis of the microstructural evolution during the ageing of pyrolysis oils from biomass. *American Chemical Society*, *22*, 306–312.

Gani, A., & Naruse, I. (2007). Effect of cellulose and lignin content on pyrolysis and combustion characteristics for several types of biomass. *Renewable Energy*, *32*(4), 649–661. https://doi.org/10.1016/j.renene.2006.02.017

Garca-Pèrez, M., Chaala, A., & Roy, C. (2002). Vacuum pyrolysis of sugarcane bagasse. *Journal of Analytical and Applied Pyrolysis*, *65*(2), 111–136. https://doi.org/10.1016/S0165-2370(01)00184-X

Garcia-Perez, M., Chaala, A., Pakdel, H., Kretschmer, D., & Roy, C. (2007). Characterization of bio-oils in chemical families. *Biomass and Bioenergy*, *31*(4), 222–242. Retrieved from http://www.sciencedirect.com/science/article/pii/S0961953406001838

Garcia-Perez, M., Adams, T.T., Goodrum, J.W., Geller, D.P., & Das, K. C. (2007). Production and Fuel Properties of Pine Chip Bio-oil / Biodiesel Blends. *Energy*, (10), 2363–2372.

Garcia-Perez, M., Wang, X.S., Shen, J., Rhodes, M.J., Tian, F., Lee, W., Wu, H., & Li, C. (2008). Fast Pyrolysis of Oil Mallee Woody Biomass: Effect of Temperature on the Yield and Quality of Pyrolysis Products. *Industrial & Engineering Chemistry Research*, *47*(6), 1846–1854. https://doi.org/10.1021/ie071497p

Ghafoori, S. (2013). *Modeling, Simulation and Optimization of Advanced Oxidation Processes for Treatment of Polymeric*. Thesis of Doctor of Philosophy, Program of Chemical Engineering, Toronto, Ontario, Canada.

Goh, C.S., Tan, K.T., Lee, K.T., & Bhatia, S. (2010). Bio-ethanol from lignocellulose: Status, perspectives and challenges in Malaysia. *Bioresource Technology*, *101*(13), 4834–4841. https://doi.org/10.1016/j.biortech.2009.08.080

Gupta, A.K., & Lilley, D.G. (2003). Thermal Destruction of Wastes and Plastics. In *Plastics and Environment* (pp. 629–696). Wiley-Interscience.

Hamelinck, C.N., Van Hooijdonk, G., & Faaij, A.P.C. (2005). Ethanol from lignocellulosic biomass: Techno-economic performance in short-, middle- and long-term. *Biomass and Bioenergy*, *28*(4), 384–410. https://doi.org/10.1016/j.biombioe.2004.09.002

Harinen, S. (2004). *Analysis of the top phase fraction of wood pyrolysis liquids*. University of Jyväskylä.

Heidari, A., Stahl, R., Younesi, H., Rashidi, A., Troeger, N., & Ghoreyshi, A.A. (2014). Effect of process conditions on product yield and composition of fast pyrolysis of Eucalyptus grandis in fluidized bed reactor. *Journal of Industrial and Engineering Chemistry*, *20*(4), 2594–2602. https://doi.org/10.1016/j.jiec.2013.10.046

Heo, H.S., Park, H.J., Yim, J., Sohn, J. M., Park, J., Kim, S., Ryu, C., Jeon, J., & Park, Y. (2010). Influence of operation variables on fast pyrolysis of Miscanthus sinensis var. purpurascens. *Bioresource Technology*, *101*(10), 3672–3677. https://doi.org/10.1016/j.biortech.2009.12.078

Heo, H.S., Park, H.J., Park, Y., Ryu, C., Suh, D.J., Suh, Y., Yim, J., & Kim, S. (2010). Bio-oil production from fast pyrolysis of waste furniture sawdust in a fluidized bed. *Bioresource Technology*, *101 Suppl*(1), S91-6. https://doi.org/10.1016/j.biortech.2009.06.003

Hu, S., Jiang, L., Wang, Y., Su, S., Sun, L., Xu, B., He, L., & Xiang, J. (2015). Effects of inherent alkali and alkaline earth metallic species on biomass pyrolysis at different temperatures. *Bioresource Technology*, *192*, 23–30. https://doi.org/10.1016/j.biortech.2015.05.042

Ingram, L., Mohan, D., Bricka, M., Steele, P., Strobel, D., Crocker, D., Mitchell, B., Mohammad, J., Cantrell, K., & Pittman, C. U. (2008). Pyrolysis of wood and bark in an auger reactor: Physical properties and chemical analysis of the produced bio-oils. *Energy and Fuels*, *22*(1), 614–625. https://doi.org/10.1021/ef700335k

Isahak, W.N.R.W., Hisham, M.W.M., Yarmo, M.A., & Yun Hin, T. (2012). A review on bio-oil production from biomass by using pyrolysis method. *Renewable and Sustainable Energy Reviews*, *16*(8), 5910–5923. https://doi.org/10.1016/j.rser.2012.05.039

Islam, M.N., & Ani, F.N. (1998). Pyrolytic oil from fluidised bed pyrolysis of oil palm shell and its characterisation. *Renewable Energy 06*, *17*, 73–84.

Jendoubi, N., Broust, F., Commandre, J.M., Mauviel, G., Sardin, M., & Lédé, J. (2011). Inorganics distribution in bio oils and char produced by biomass fast pyrolysis: The key role of aerosols. *Journal of Analytical and Applied Pyrolysis*, *92*(1), 59–67. https://doi.org/10.1016/j.jaap.2011.04.007

Jiang, H., Song, L., Cheng, Z., Chen, J., Zhang, L., Zhang, M., Hu, M., Li, J., & Li, J. (2015). Influence of pyrolysis condition and transition metal salt on the product yield and characterization via Huadian oil shale pyrolysis. *Journal of Analytical and Applied Pyrolysis*, *112*, 230–236. https://doi.org/10.1016/j.jaap.2015.01.020

Kan, T., Strezov, & Evans, T.J. (2016). Lignocellulosic biomass pyrolysis: A review of product properties and effects of pyrolysis parameters. *Renewable and Sustainable Energy Reviews*, *57*, 126–1140. https://doi.org/10.1016/j.rser.2015.12.185

Kang, B.S., Lee, K.H., Park, H.J., Park, Y.K., & Kim, J.S. (2006). Fast pyrolysis of radiata pine in a bench scale plant with a fluidized bed: Influence of a char separation system and reaction conditions on the production of bio-oil. *Journal of Analytical and Applied Pyrolysis*, *76*(1–2), 32–37. https://doi.org/10.1016/j.jaap.2005.06.012

Kersten, S.R.A., Van Swaaij, W.P.M., Lefferts, L., & Seshan, K. (2007). Chapter 6. Options for Catalysis in the Thermochemical Conversion of Biomass into Fuels. In *Catalysis for Renewables: from feedstock to Energy Production*. Wiley-VCH.

Kim, S.W., Koo, B.S., Ryu, J.W., Lee, J.S., Kim, C.J., Lee, D.H., Kim, G.R., & Choi, S. (2013). Bio-oil from the pyrolysis of palm and Jatropha wastes in a fluidized bed. *Fuel Processing Technology*, *108*, 118–124. https://doi.org/10.1016/j.fuproc.2012.05.002

Kleen, M., & Gellerstedt, G. (1995). Influence of inorganic species on the formation of polysaccharide and lignin degradation products in the analytical pyrolysis of pulps. *Journal of Analytical and Applied Pyrolysis*, *35*(1), 15–41. https://doi.org/10.1016/0165-2370(95)00893-J

Koenig, J. A. (n.d.). Amount and Concentration : Making and Diluting Solutions. Retrieved December 30, 2015, from http://www.mathcentre.ac.uk/resources/uploaded/module2textbooklike.pdf

Krishna Prasad K., Sangen, E., & Visser, P. (1985). Woodburning Cookstoves. In *Advances in Heat Transfer* (pp. 159–310).

Larson, D. (2008). Biofuel production technologies: Status, prospects and implications for trade and development. *United Nations Conference on Trade and Development*, 1–41.

Lédé, J., Broust, F., Ndiaye, F.T., & Ferrer, M. (2007). Properties of bio-oils produced by biomass fast pyrolysis in a cyclone reactor. *Fuel*, *86*(12–13), 1800–1810. https://doi.org/10.1016/j.fuel.2006.12.024

Lehto, J., Oasmaa, A., Solantausta, Y., Kytö, M., & Chiaramonti, D. (2013). Fuel oil quality and combustion of fast pyrolysis bio-oils. *VTT Publications*, (87), 79. https://doi.org/http://dx.doi.org/10.1016/j.apenergy.2013.11.040

Liew, W.H., Hassim, M.H., & Ng, D.K.S. (2014). Review of evolution, technology and sustainability assessments of biofuel production. *Journal of Cleaner Production*. https://doi.org/10.1016/j.jclepro.2014.01.006

Lu, Q., Li, W-Z., & Zhu, X-F. (2009). Overview of fuel properties of biomass fast pyrolysis oils. *Energy Conversion and Management*, *50*(5), 1376–1383. https://doi.org/10.1016/j.enconman.2009.01.001

Lu, Q., Yang, X-C., Dong, C-Q., Zhang, Z-F., Zhang, X-M., & Zhu, X-F. (2011). Influence of pyrolysis temperature and time on the cellulose fast pyrolysis products: Analytical Py-GC/MS study. *Journal of Analytical and Applied Pyrolysis*, *92*(2), 430–438. Retrieved from http://www.sciencedirect.com/science/article/pii/S0165237011001495

Luo, Z., Wang, S., Liao, Y., Zhou, J., Gu, Y., & Cen, K. (2004). Research on biomass fast pyrolysis for liquid fuel. *Biomass and Bioenergy*, *26*(5), 455–462. https://doi.org/10.1016/j.biombioe.2003.04.001

Lv, D., Xu, M., Liu, X., Zhan, Z., Li, Z., & Yao, H. (2010). Effect of cellulose, lignin, alkali and alkaline earth metallic species on biomass pyrolysis and gasification. *Fuel Processing Technology*, *91*(8), 903–909. https://doi.org/10.1016/j.fuproc.2009.09.014

Malaysia Energy Centre. (2002). Retrieved June 24, 2015, from www.ptm.org.my

Mamleeva, V., Bourbigot, S., Le Bras, M., & Yvon, J. (2009). The facts and hypotheses relating to the phenomenological model of cellulose pyrolysis: Interdependence of the steps. *J. Anal. Appl. Pyrolysis*, *84*(1), 1–17.

Mayer, Z.A., Apfelbacher, A., & Hornung, A. (2012). Effect of sample preparation on the thermal degradation of metal-added biomass. *Journal of Analytical and Applied Pyrolysis*, *94*, 170–176. https://doi.org/10.1016/j.jaap.2011.12.008

Mazlan, M.A.F., Uemura, Y., Osman, N.B., & Yusup, S. (2015). Fast pyrolysis of hardwood residues using a fixed bed drop-type pyrolyzer. *Energy Conversion and Management*, *98*, 208–214. https://doi.org/10.1016/j.enconman.2015.03.102

McGrath, T.E., Chan, W.G., & Hajaligol, M.R. (2003). Low temperature mechanism for the formation of polycyclic aromatic hydrocarbons from the pyrolysis of cellulose. *Journal of Analytical and Applied Pyrolysis*, *66*(1–2), 51–70. https://doi.org/10.1016/S0165-2370(02)00105-5

Meier, D. (1999). New methods for chemical and physical characterization and round robin testing. In *Fast Pyrolysis of Bomass: A Handbook*. Newburry: CPL Press.

Meier, S. (2013). Elemental Analysis of Wood Fuels NYSERDA's Promise to New Yorkers: NYSERDA provides resources, expertise and objective information so New Yorkers can make confident, informed energy decisions . *NYSERDA Report 13-13*, (June).

Mekhilef, S., Saidur, R., Safari, A., & Mustaffa, W.E.S.B. (2011). Biomass energy in Malaysia: Current state and prospects. *Renewable and Sustainable Energy Reviews*, *15*(7), 3360–3370. https://doi.org/10.1016/j.rser.2011.04.016

Michael, L.B., Jack, B.H., John, P.L. and William, A.P. (1989). Heterogeneous cracking of wood pyrolysis tars over fresh wood char surfaces. *Energy Fuels*, *3*(6), 735–740.

Michael, H.K., John, N., Christopher, J., & Nachtsheim, W.W. (2011). *No Title* (4th editio). McGraw-Hill Education.

Mofijur, M., Masjuki, H.H., Kalam, M.A., Hazrat, M.A., Liaquat, A.M., Shahabuddin, M., & Varman, M. (2012). Prospects of biodiesel from Jatropha in Malaysia. *Renewable and Sustainable Energy Reviews*, *16*(7), 5007–5020. https://doi.org/10.1016/j.rser.2012.05.010

Mohan, D., Pittman, C.U., & Steele, P.H. (2006). Pyrolysis of Wood/Biomass for Bio-oil: A Critical Review. *Energy & Fuels*, *20*(3), 848–889. https://doi.org/10.1021/ef0502397

Montgomery, D.C. (2012). Design and Analysis of Experiments (8th Editio). John-Wiley & Sons. Inc. Tempe, Arizona.

Morf, P., Hasler, P., & Nussbaumer, T. (2002). Mechanisms and kinetics of homogeneous secondary reactions of tar from continuous pyrolysis of wood chips. *Fuel*, *81*(7), 843–853. Retrieved from http://www.sciencedirect.com/science/article/pii/S0016236101002162

Mourant, D., Wang, Z., He, M., Wang, X.S., Garcia-Perez, M., Ling, K., & Li, C-Z. (2011). Mallee wood fast pyrolysis: Effects of alkali and alkaline earth metallic species on the yield and composition of bio-oil. *Fuel*, *90*(9), 2915–2922. https://doi.org/10.1016/j.fuel.2011.04.033

Mszros, E., Vrhegyi, G., Jakab, E., & Marosvlgyi, B. (2004). Thermogravimetric and Reaction Kinetic Analysis of Biomass Samples from an Energy Plantation Thermogravimetric and Reaction Kinetic Analysis of Biomass Samples from an Energy Plantation. *Review Literature And Arts Of The Americas*, (10), 497–507. https://doi.org/10.1021/ef034030

Mullen, C.A., & Boateng, A.A. (2011). Characterization of water insoluble solids isolated from various biomass fast pyrolysis oils. *Journal of Analytical and Applied Pyrolysis*, *90*(2), 197–203. Retrieved from http://www.sciencedirect.com/science/article/pii/S0165237010001798

Naik, S.N., Goud, V.V., Rout, P.K., & Dalai, A.K. (2010). Production of first and second generation biofuels: A comprehensive review. *Renewable and Sustainable Energy Reviews*, *14*(2), 578–597. https://doi.org/10.1016/j.rser.2009.10.003

Nanda, S., Kozinski, J.A., & Dalai, A. K. (2016). Lignocellulosic biomass: A review of conversion technologies and fuel products. *Current Biochemical Engineering*, *3*(1), 24–36. https://doi.org/10.2174/2213385203666150219232000

Neves, D., Thunman, H., Matos, A., Tarelho, L., & Gómez-Barea, A. (2011). Characterization and prediction of biomass pyrolysis products. *Progress in Energy and Combustion Science*, *37*(5), 611–630. https://doi.org/10.1016/j.pecs.2011.01.001

Ngo, T-A., Kim, J., & Kim, S-S. (2013). Fast pyrolysis of palm kernel cake using a fluidized bed reactor: Design of experiment and characteristics of bio-oil. *Journal of Industrial and Engineering Chemistry*, *19*(1), 137–143. https://doi.org/10.1016/j.jiec.2012.07.015

Nigam, P.S., & Singh, A. (2011). Production of liquid biofuels from renewable resources. *Progress in Energy and Combustion Science*, *37*(1), 52–68. https://doi.org/10.1016/j.pecs.2010.01.003

Nik-Azar, M., Hajaligol, M.R., Sorahbi, M., & Dabir, B. (1996). Mineral matter effects in rapid pyrolysis of beech wood. *Fuel Processing Technology*, *3820*(96), 7–17.

Nowakowski, D.J., Bridgwater, A.V., Elliott, D.C., Meier, D., & de Wild, P. (2010). Lignin fast pyrolysis: Results from an international collaboration. *Journal of Analytical and Applied Pyrolysis*, *88*(1), 53–72. https://doi.org/10.1016/j.jaap.2010.02.009

Nowakowski, D.J., Jones, J.M., Brydson, R.M.D., & Ross, A.B. (2007). Potassium catalysis in the pyrolysis behaviour of short rotation willow coppice. *Fuel*, *86*(15), 2389–2402. https://doi.org/10.1016/j.fuel.2007.01.026

Nurbakhsh Said. (1989). *Thermal Decomposition of Charring Materials*. Michigan State University.

Oasmaa, A., Leppamaki, E., Koponen, P., Levander, J., & Tapola, E. (1997). Physical characterisation of biomass-based pyrolysis liquids application of standard fuel oil analyses. *VTT Publications*, (306). https://doi.org/10.1016/S0140-6701(98)97220-4

Oasmaa, A., & Czernik, S. (1999). Fuel oil quality of biomass pyrolysis oil - State of the art for the end users. *Energy & Fuels*, *13*(4), 914–921. https://doi.org/10.1021/ef980272b

Oasmaa, A., & Peacocke, C. (2001). A guide to physical property characterisation of biomass-derived fast pyrolysis liquids. *VTT Publications*, (450), 2–65.

Oasmaa, A., Kuoppala, E., Gust, S., & Solantausta, Y. (2003). Fast pyrolysis of forestry residue. 1. Effect of extractives on phase separation of pyrolysis liquids. *Energy and Fuels*, *17*(1), 1–12. https://doi.org/10.1021/ef020088x

Oasmaa, A., Kuoppala, E., & Solantausta, Y. (2003). Fast pyrolysis of forestry residue. 2. Physicochemical composition of product liquid. *Energy and Fuels*, *17*(2), 433–443. https://doi.org/10.1021/ef020206g

Oasmaa, A., & Kuoppala, E. (2003). Fast Pyrolysis of Forestry Residue. 3. Storage Stability of Liquid Fuel. *Energy & Fuels*, *17*(4), 1075–1084.

Oasmaa, A., Elliott, D.C., & Muller, S. (2009). Quality control in fast pyrolysis bio-oil production and use. *Environmental Progress and Sustainable Energy*, *28*(3), 404–409. https://doi.org/10.1002/ep.10382

Onay, O. (2007). Influence of pyrolysis temperature and heating rate on the production of bio-oil and char from safflower seed by pyrolysis, using a well-swept fixed-bed reactor. *Fuel Processing Technology*, *88*(5), 523–531. https://doi.org/10.1016/j.fuproc.2007.01.001

Ong, H.C., Mahlia, T.M.I., & Masjuki, H.H. (2011). A review on energy scenario and sustainable energy in Malaysia. *Renewable and Sustainable Energy Reviews*, *15*(1), 639–647. https://doi.org/10.1016/j.rser.2010.09.043

Ortega, J.V., Renehan, A.M., Liberatore, M.W., & Herring, A.M. (2011). Physical and chemical characteristics of aging pyrolysis oils produced from hardwood and softwood feedstocks. *Journal of Analytical and Applied Pyrolysis*, *91*(1), 190–198. https://doi.org/10.1016/j.jaap.2011.02.007

Ozcimen, D., & Karaosmanoglu, F. (2004). Production and characterization of bio-oil and biochar from rapeseed cake. *Renewable Energy*, *29*(5), 779–787.

Park, H.J., Dong, J-I., Jeon, J-K., Park, Y-K., Yoo, K-S., Kim, S-S., Kim, J., & Kim, S. (2008). Effects of the operating parameters on the production of bio-oil in the fast pyrolysis of Japanese larch. *Chemical Engineering Journal*, *143*(1–3), 124–132. https://doi.org/10.1016/j.cej.2007.12.031

Park, H.J., Park, Y-K., Dong, J-I., Kim, J-S., Jeon, J-K., Kim, S-S., Kim, J., Song, B., Park, J., & Lee, K-J. (2009). Pyrolysis characteristics of Oriental white oak: Kinetic study and fast pyrolysis in a fluidized bed with an improved reaction system. *Fuel Processing Technology*, *90*(2), 186–195. https://doi.org/10.1016/j.fuproc.2008.08.017

Part 1: Literature Review and Model Simulations. (2005). In *Biomass Fast Pyrolysis in a Fluidized Bed: Product Cleaning by In-situ Filtration* (pp. 8773–8785).

Radlein, D. (2002). Study of levoglucosan production – a review biomass. In *A Handbook: Fast pyrolysis of biomass. Vol. 2*. Newburry: CPL Press.

Ran Xu. (2010). *Development of advanced technologies for biomass pyrolysis*. (Doctoral Desertation). The University of Western Ontario, London, Ontario.

Rath, J., Wolfinger, M.G., & Stainer, G. (2003). Heat of Wood Pyrolysis. *Fuel*, *82*(1), 81–91.

Raveendran, K., Ganesh, A., & Khilart, K.C. (1995). Influence of mineral matter pyrolysis characteristics on biomass, *74*(12), 1812–1822.

Richards, G. N. and Zheng, G. (1991). Influence of Metal Ion and Salts on the Products from Pyrolysis of Wood: Application to Thermochamical Processing of Newspring and Biomass. *J. Anal. Appl. Pyrolysis*, *21*(1–2), 133–146.

Rowell, R.M. (1984). The Chemistry of Solid Wood.

Scheirs, J., Camino, G., & Tumiatti, W. (2001). Overview of water evolution during the thermal degradation of cellulose. *European Polymer Journal*, *37*(5), 933–942. https://doi.org/10.1016/S0014-3057(00)00211-1

Scott, D.S., Piskorz, J. (1984). The Continuous Flash Pyrolysis of Biomass. *J. Chem. Eng*, *62*(3), 404–412.

Scott, D.S., Majerski, P., Piskorz, J., & Radlein, D. (1999). A second look at fast pyrolysis of biomass—the RTI process. *Journal of Analytical and Applied Pyrolysis*, *51*(1–2), 23–37. https://doi.org/10.1016/S0165-2370(99)00006-6

Scott, D.S., Paterson, L., Piskorz, J., & Radlein, D. (2000). Pretreatment of poplar wood for fast pyrolysis: Rate of cation removal. *Journal of Analytical and Applied Pyrolysis*, *57*(2), 169–176. https://doi.org/10.1016/S0165-2370(00)00108-X

Shafizadeh, F. (1982). Introduction to pyrolysis of biomass. *Journal of Analytical and Applied Pyrolysis*, *3*(4), 283–305.

Shafizadeh, F., Furneaux, R.H., Cochran, T.G., Scholl, J.P., & Sakai, Y. (1979). Production of levoglucosan and glucose from pyrolysis of cellulosic materials. *Journal of Applied Polymer Science*, *23*(12), 3525–3539. https://doi.org/10.1002/app.1979.070231209

Sharma, R.K., Wooten, J.B., Baliga, V.L., Lin, X., Geoffrey Chan, W., & Hajaligol, M. R. (2004). Characterization of chars from pyrolysis of lignin. *Fuel*, *83*(11–12), 1469–1482. https://doi.org/10.1016/j.fuel.2003.11.015

Shen, J., Wang, X-S., Garcia-Perez, M., Mourant, D., Rhodes, M.J., & Li, C-Z. (2009). Effects of particle size on the fast pyrolysis of oil mallee woody biomass. *Fuel*, *88*(10), 1810–1817. https://doi.org/10.1016/j.fuel.2009.05.001

Shen, D.K., Gu, S., & Bridgwater, A.V. (2010). Study on the pyrolytic behaviour of xylan-based hemicellulose using TG-FTIR and Py-GC-FTIR. *Journal of Analytical and Applied Pyrolysis*, *87*(2), 199–206. https://doi.org/10.1016/j.jaap.2009.12.001

Shihadeh A., & H. S. (2002). Impact of Biomass Pyrolysis Oil Process Conditions on Ignition Delay in Compression Ignition Engines. *Energy & Fuels*, *16*(3), 552–561.

Sinha, S., Jhalani, A., Ravi, M. R., & Ray, A. (2000). Modelling of Pyrolysis in Wood : A Review. *Journal of Solar Energy Sosiety of India (SESI)*, *10 (1)*, 41–62.

Sudo, S., Takahashi, F., & Tekeuchi, M. (1989). *Chemical Properties of Biomass*. (A. H. C. W. Kitani, O, Ed.). New York: Gordon and Breach Science.

The Japan Institute of Energy. (2010). Bahagian 7: Situasi biojisim di negara- negara Asia. In *The Asian Biomass Handbook: A Guide for Biomass Production and Utilization* (pp. 200–243).

Tillman, D. A. (1991). *The Combustion of Solid Fuels and Wastes*. ACADEMIC PRESS. INC.

Timber Wood Supply. (2017). Retrieved November 23, 2017, from http://timberwoodsupplymalaysia.com.my/

Tröger, N., Richter, D., & Stahl, R. (2013). Effect of feedstock composition on product yields and energy recovery rates of fast pyrolysis products from different straw types. *Journal of Analytical and Applied Pyrolysis*, *100*, 158–165. https://doi.org/10.1016/j.jaap.2012.12.012

Uzun, B.B., Pütün, A.E., & Pütün, E. (2007). Composition of products obtained via fast pyrolysis of olive-oil residue: Effect of pyrolysis temperature. *Journal of Analytical and Applied Pyrolysis*, *79*(1–2 SPEC. ISS.), 147–153. https://doi.org/10.1016/j.jaap.2006.12.005

Vaca Garcia, C. (2008). Biomaterials. In J. C. and F. Deswarte (Ed.), *Introduction to Chemicals from Biomass*. John-Wiley and Sons, Ltd.

Vamvuka, D. (2011). Bio-oil, solid and gaseous biofuels from biomass pyrolysis processes - An overview. *International Journal of Energy Research*, *35*(10), 835–862.

Van de Velden, M., Baeyens, J., Brems, A., Janssens, B., & Dewil, R. (2010). Fundamentals, kinetics and endothermicity of the biomass pyrolysis reaction. *Renewable Energy*, *35*(1), 232–242. Retrieved from http://www.sciencedirect.com/science/article/pii/S0960148109001803

Várhegyi, G., Grønli, M.G., & Di Blasi, C. (2004). Effects of Sample Origin, Extraction, and Hot-Water Washing on the Devolatilization Kinetics of Chestnut Wood. *Industrial & Engineering Chemistry Research*, *43*(10), 2356–2367. https://doi.org/10.1021/ie034168f

Venderbosch, R.H., & Prins, W. (2011). Fast Pyrolysis. In *Wiley Series in Renewable Resource : Thermochemical Processing of Biomass : Conversion into Fuels, Chemicals and Power*. (pp. 124–156). John Wiley and Sons, Ltd.

Vick, C.B. (2007). Adhesive Bonding of Wood Materials. In U. S. Department ofAgriculture (Ed.), *The Encyclopedia of Wood* (p. 2). Skyhorse Publishing, Inc. Delaware corporation.

Vigouroux, R.Z. (2001). *Pyrolysis of Biomass*. Faculty of Mississipi State University.

Wang, X., Kersten, S.R.A., Prins, W., Van Swaaij, & Wim, P.M. (2005). Biomass Pyrolysis in a Fluidized Bed Reactor. Part 2: Experimental Validation of Model Results. *Ind. Eng. Chem. Res.*, *44*(23), 8786–8795. https://doi.org/10.1021/ie050486y

Wang, K., Zhang, J., Shanks, B.H., & Brown, R.C. (2015). The deleterious effect of inorganic salts on hydrocarbon yields from catalytic pyrolysis of lignocellulosic biomass and its mitigation. *Applied Energy*, *148*, 115–120. https://doi.org/10.1016/j.apenergy.2015.03.034

Wang, P., Zhan, S., Yu, H., Xue, X., & Hong, N. (2010). The effects of temperature and catalysts on the pyrolysis of industrial wastes (herb residue). *Bioresource Technology*, *101*(9), 3236–3241. https://doi.org/10.1016/j.biortech.2009.12.082

Water and Energy Consumer Association of Malaysia. (2009). Retrieved June 24, 2015, from www.ptm.org.my/cabd/pdf/GreenTechnologyWaterEnergySector.pdf

Wei, L., Xu, S., Zhang, L., Zhang, H., Liu, C., Zhu, H., & Liu, S. (2006). Characteristics of fast pyrolysis of biomass in a free fall reactor. *Fuel Processing Technology*, *87*(10), 863–871. https://doi.org/10.1016/j.fuproc.2006.06.002

Wildschut, J. (2009). Chapter 1: An Introduction to the Hydroprocessing of Biomass Derived Pyrolysis oil. In *Pyrolysis oil upgrading to transportation fuels by catalytic hydrotreatment.* (pp. 5–9). University of Groningen. Retrieved from http://www.rug.nl/research/portal

Xiu, S., & Shahbazi, A. (2012). Bio-oil production and upgrading research: A review. *Renewable and Sustainable Energy Reviews*, *16*(7), 4406–4414. https://doi.org/10.1016/j.rser.2012.04.028

Xu, J., Jiang, J., Chen, J., & Sun, Y. (2010). Biofuel production from catalytic cracking of woody oils. *Bioresource Technology*, *101*(14), 5586–5591. https://doi.org/10.1016/j.biortech.2010.01.148

Yang, H., Yan, R., Chen, H., Lee, D.H., & Zheng, C. (2007). Characteristics of hemicellulose, cellulose and lignin pyrolysis. *Fuel*, *86*(12–13), 1781–1788. https://doi.org/10.1016/j.fuel.2006.12.013

Zafar, S. (2011). Biomass Energy in Malaysia. Retrieved April 23, 2015, from http://cleantechsolutions.wordpress.com/2011/07/15

Zafar, S. (2015). Biomass Resources in Malaysia. Retrieved June 26, 2015, from http://www.bioenergyconsult.com/biomass-energy-malaysia/

Zaror, C.A., & Pyle, D.L. (1982). The pyrolysis of biomass: A general review. *Proceedings of the Indian Academy of Science (Engg. Sci.)*, *5*(December), 269–285.

Zhang, L., Liu, R., Yin, R., & Mei, Y. (2013). Upgrading of bio-oil from biomass fast pyrolysis in China: A review. *Renewable and Sustainable Energy Reviews*, *24*, 66–72. https://doi.org/10.1016/j.rser.2013.03.027

Zhang, J. (1996). *Pyrolysis of Biomass*. Thesis of Master Degree of Science, Chemical Engineering, Mississippi State University.

Zhang, Q., Chang, J., Wang, T., & Xu, Y. (2007). Review of biomass pyrolysis oil properties and upgrading research. *Energy Conversion and Management*, *48*(1), 87–92. https://doi.org/10.1016/j.enconman.2006.05.010